SDS No.

18543



SAFETY DATA SHEET LEAD SUBSTITUTE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME LEAD SUBSTITUTE PRODUCT NO. QFS300, QFS301

INTERNAL ID

APPLICATION Fuel additive.

SUPPLIER TETROSYL LIMITED

BEVIS GREEN WORKS

WALMERSLEY

BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com

2 HAZARDS IDENTIFICATION

Harmful: may cause lung damage if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xn;R65. R52/53.

HUMAN HEALTH

See section 11 for additional information on health hazards.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
DISTILLATES (PETROLEUM) HYDROTREATED LIGHT	265-149-8	64742-47-8	60-100%	Xn;R65.
KEROSENE	232-366-4		1-5%	Xn;R65. Xi;R38. R10.
NAPHTHALENE	202-049-5		<0.5	Xn;R22. Carc. Cat. 3;R40. F;R11. N;R50/53.
PETROLEUM DISTILLATES (MINERAL SPIRIT)	265-185-4	64742-82-1	<1%	Xn;R65. N;R51/53. R10,R66.
PETROLEUM NAPHTHA	265-198-5		1-5%	Xn;R65. Xi;R36/38. N;R51/53.
POTASSIUM CARBOXYLATE			1-5%	Xi;R36/38. R52.

The Full Text for all R-Phrases is Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Remove affected person from source of contamination. Get medical attention immediately!

INHALATION

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place.

Report Date: 15/08/2011 2 / 5
REVISION DATE 24/03/2011 SDS No. 18543

LEAD SUBSTITUTE

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice. Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to hospital or eye specialist.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Beware, risk of formation of toxic and corrosive gases.

SPECIFIC HAZARDS

In case of fire, toxic and corrosive gases may be formed.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

ENVIRONMENTAL PRECAUTIONS

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures. Absorb spillage with non-combustible, absorbent material. Ventilate well. Prevent discharge of larger quantity to drain.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
DISTILLATES (PETROLEUM)	WEL		1000			
HYDROTREATED LIGHT			mg/m3			

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT

Report Date: 15/08/2011 3 / 5
REVISION DATE 24/03/2011 SDS No. 18543

LEAD SUBSTITUTE







PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

Wear suitable respiratory protection. Check that mask fits tight and change filter regularly.

HAND PROTECTION

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Protection against this substance requires special consideration.

EYE PROTECTION

Wear tight-fitting goggles or face shield.

OTHER PROTECTION

Provide eyewash station. AVOID ALL SKIN AND RESPIRATORY CONTACT!

HYGIENE MEASURES

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.

SKIN PROTECTION

Protection suit must be worn.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Clear liquid.

COLOUR Orange.

BOILING POINT (°C) 175°C

RELATIVE DENSITY 0.84

FLASH POINT (°C) >55°C

10 STABILITY AND REACTIVITY

STABILITY

No particular stability concerns.

11 TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

This chemical can be hazardous when inhaled and/or touched. This chemical may cause skin/eye irritation and burns (corrosive). May cause severe internal injury. Vapour from this chemical can be hazardous when inhaled.

ROUTE OF ENTRY

Inhalation. Ingestion. Skin and/or eye contact. Skin absorption.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

When handling waste, consideration should be made to the safety precautions applying to handling of the product. Only experts should be permitted to carry out disposal of this material.

Report Date : 15/08/2011 REVISION DATE 24/03/2011

LEAD SUBSTITUTE

LEAD SUBSTITU

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous

goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

ENVIRONMENTALLY

HAZARDOUS

SUBSTANCE/MARINE

POLLUTANT

15 REGULATORY INFORMATION

LABELLING



Harmful

No.

CONTAINS DISTILLATES (PETROLEUM) HYDROTREATED LIGHT

RISK PHRASES

R52/53 Harmful to aquatic organisms, may cause long-term adverse

SDS No.

18543

effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

SAFETY PHRASES

S2 Keep out of the reach of children.

S13 Keep away from food, drink and animal feeding stuffs.

S46 If swallowed, seek medical advice immediately and show this

container or label.

S56 Dispose of this material and its container to hazardous or

special waste collection point.

Detergent Labelling:

>= 30% Aromatic hydrocarbons.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

16 OTHER INFORMATION

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

REVISION DATE 24/03/2011

REV. NO./REPL. SDS 4

GENERATED

Report Date: 15/08/2011 5 / 5
REVISION DATE 24/03/2011 SDS No. 18543

LEAD SUBSTITUTE

RISK PHRASES IN FULL

R10 Flammable

R22 Harmful if swallowed.

R52 Harmful to aquatic organisms.

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R40 Limited evidence of a carcinogenic effect.

R66 Repeated exposure may cause skin dryness or cracking.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

DISCLAIMER

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.