o. 16038



SAFETY DATA SHEET PENETRATING OIL

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME PENETRATING OIL

PRODUCT NO. XOP125
INTERNAL ID HFL

APPLICATION Universal lubricant.
SUPPLIER TETROSYL LIMITED

BEVIS GREEN WORKS

WALMERSLEY

BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com

EMERGENCY TELEPHONE 0161 764 5981

2 HAZARDS IDENTIFICATION

Harmful: may cause lung damage if swallowed.

CLASSIFICATION (1999/45) Xn;R65.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
(Z-)-N-METHYL-N-		110-25-8	<0.5	Xi;R41,R38. N;R50/53.
(1-OXO-9-OCTADECENYL)-GLYCINE				
Distillates (Petroleum), Hydrotreated Light;	265-149-8	64742-47-8	60-100%	Xn;R65
Kerosine - Unspecified				

The Full Text for all R-Phrases is Displayed in Section 16

The Full Text for all R-Phrases is Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Remove affected person from source of contamination. NOTE! Effects may be delayed. Keep affected person under observation. Move the exposed person to fresh air at once. NOTE! Keep affected person away from heat, sparks and flames! Place unconscious person on the side in the recovery position and ensure breathing can take place. Keep the affected person warm and at rest. Get prompt medical attention.

NOTES TO THE PHYSICIAN

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

INHALATION

Remove victim immediately from source of exposure. Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions.

Report Date: 04/01/2012 2 / 5
REVISION DATE 17/08/2005 SDS No. 16038

PENETRATING OIL

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions. Do not give victim anything to drink if he is unconscious. NOTE! Keep affected person away from heat, sparks and flames!

SKIN CONTACT

Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention if any discomfort continues.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

No specific fire fighting procedure given.

UNUSUAL FIRE & EXPLOSION HAZARDS

May form explosive mixture with air at very high concentration.

SPECIFIC HAZARDS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

In case of inadequate ventilation, use respiratory protection. Do not smoke, use open fire or other sources of ignition. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces. For personal protection, see section 8. Avoid inhalation of vapours and contact with skin and eyes.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground. Prevent entry into drains. Avoid discharge to the aquatic environment. The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Cover large spillages with alcohol-resistant foam. Absorb with inert, damp, non-combustible material, then flush area with water. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Observe good chemical hygiene practices. Mechanical ventilation or local exhaust ventilation may be required. Provide good ventilation.

STORAGE PRECAUTIONS

Keep containers tightly closed. Keep upright. Keep in original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Report Date: 04/01/2012 3 / 5
REVISION DATE 17/08/2005 SDS No. 16038

PENETRATING OIL







ENGINEERING MEASURES

Observe occupational exposure limits and minimize the risk of inhalation of vapours. Provide adequate ventilation.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided. Use respiratory equipment with gas filter, type A2.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Nitrile gloves are recommended.

EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

OTHER PROTECTION

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES

When using do not eat, drink or smoke. Wash hands after contact. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash contaminated clothing before reuse.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Coloured liquid.

COLOUR Black. FLASH POINT (°C) 38

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

None under normal conditions.

11 TOXICOLOGICAL INFORMATION

TOXIC DOSE 1 - LD 50 >5000 (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSINE -

UNSPECIFIED) mg/kg (oral rat)

TOXIC CONC. - LC 50 5200 (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSINE -

UNSPECIFIED) mg/m3/30h (inh-rat)

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

INGESTION

Harmful: may cause lung damage if swallowed.

HEALTH WARNINGS

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Report Date: 04/01/2012 REVISION DATE 17/08/2005

PENETRATING OIL

SDS No. 16038

ROUTE OF ENTRY

Ingestion.

MEDICAL CONSIDERATIONS

Risk of chemical pneumonia after aspiration.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

LC 50, 96 Hrs, FISH mg/l

2200 (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSINE -

UNSPECIFIED)

BIOACCUMULATION

No data available on bioaccumulation.

DEGRADABILITY

There are no data on the degradability of this product.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

DISPOSAL METHODS

Confirm disposal procedures with environmental engineer and local regulations.

14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous

goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

ENVIRONMENTALLY

HAZARDOUS

SUBSTANCE/MARINE

POLLUTANT

ADR LABEL NO. 0

15 REGULATORY INFORMATION

LABELLING



Harmful

No.

CONTAINS Distillates (Petroleum), Hydrotreated Light; Kerosine - Unspecified

RISK PHRASES

R65 Harmful: may cause lung damage if swallowed.

SAFETY PHRASES

S2 Keep out of the reach of children.

S13 Keep away from food, drink and animal feeding stuffs.

S46 If swallowed, seek medical advice immediately and show this

container or label.

S56 Dispose of this material and its container to hazardous or

special waste collection point.

Report Date: 04/01/2012 5 / 5
REVISION DATE 17/08/2005 SDS No. 16038

PENETRATING OIL

Detergent Labelling:

>= 30% Aliphatic hydrocarbons

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

16 OTHER INFORMATION

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

ISSUED BY

Health & Safety Department

REVISION DATE 17/08/2005

REV. NO./REPL. SDS 13

GENERATED

SAFETY DATA SHEET STATUS

Approved.

RISK PHRASES IN FULL

R65 Harmful: may cause lung damage if swallowed.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.